

## SEE THRU KITS

Set Size	Burner Kit Model #	Certification	BTU Input Rating	Weight (lbs)	Compatible Log Sizes	Compatible Log Styles
<b>TWO SIDED FIREPLACES (require min. 22" fireplace depth)</b>						
<b>NATURAL GAS</b>						
18"	18SNST(0A,1B,1H,2A)5	NON CERTIFIED	140,000	47	18"-21"	Fresh Cut, Charred Styles, Radiant Heat
24"	24SNST(0A,1B,1H,2A)5	NON CERTIFIED	150,000	54	24"-28"	Fresh Cut, Charred Styles, Radiant Heat
30"	30SNST(0A,1B,1H,2A)5	NON CERTIFIED	160,000	61	30"	Fresh Cut, Charred Styles, Radiant Heat
36"	36SNST(0A,1B,1H,2A)5	NON CERTIFIED	180,000	88	36"	Fresh Cut, Charred Styles, Radiant Heat
42"	42SNST(0A,1B,1H,2A)5	NON CERTIFIED	185,000	112	36"	Fresh Cut, Charred Styles, Radiant Heat

**\* IDENTIFY FACTORY INSTALLED VALVE STYLE IN THE MODEL NUMBER**

0A - NO VALVE - MATCH LIGHT

1K - VARIABLE FLAME SAFETY PILOT WITH REMOTE CONTROL

1B - SAFETY PILOT VALVE

2A - MILLIVOLT SAFETY PILOT WITH WALL SWITCH

1H - LATCH TAP SAFETY PILOT WITH REMOTE CONTROL

2B - HIGH CAPACITY MILLIVOLT SAFETY PILOT WITH WALL SWITCH

**IMPORTANT: ALL SEE THRU LIQUID PROPANE SETS REQUIRE TWO SAFETY PILOT CONTROLS**

Set Size	Burner Kit Model #	Certification	BTU Input Rating	Weight (lbs)	Compatible Log Sizes	Compatible Log Styles
<b>TWO SIDED FIREPLACES (require min. 22" fireplace depth)</b>						
<b>LIQUID PROPANE</b>						
18"	18SPST(1B,1H,2A)5	NON CERTIFIED	85,000	48	18"-21"	Fresh Cut, Charred Styles, Radiant Heat
24"	24SPST(1B,1H,2A)5	NON CERTIFIED	95,000	55	24"-28"	Fresh Cut, Charred Styles, Radiant Heat
30"	30SPST(1B,1H,2A)5	NON CERTIFIED	105,000	65	30"	Fresh Cut, Charred Styles, Radiant Heat
36"	36SPST(1B,1H,2A)5	NON CERTIFIED	120,000	89	36"	Fresh Cut, Charred Styles, Radiant Heat